




RS601 SERIES



額定電流、電壓 RATING

6A 250VAC 10A 250VAC
6(8)A 250VAC 6A/125A 250VAC
8A/128A 250VAC 6(4)A 250VAC
10A 125VAC

接觸電阻 CONTACT RESISTANCE

≤ 20mΩ

絕緣電阻 INSULATION RESISTANCE

≥ 100MΩ

介電強度 DIELECTRIC INTENSITY

≥ 1800VAC/3S

電器壽命 ELECTRICAL LIFE

≥ 10,000 Cycles

RS601	A	1	01	0	01	1	B	B
系列号 Series	基座类型 Base Type	极 Poles	电路图 circuit diagram	带灯状况 Illuminated	按钮标志 Button Mark	端子规格 Terminal Type	按钮颜色 Actuator Colour	基座颜色 Base Colour
1	A	1 Single Pole	01 ON-OFF	0 不带灯 NO Illuminated	00	1 4.8mm TAB 0.8mm THICK	B 黑色 Black	B 黑色 Black
2	AH	2 Double Pole	02 ON-ON	A 220V 氖灯(绿色) 220V Neon Lamp	01 0	2 PCB (RIGHTANGLE)	G 绿色 Green	G 绿色 Green
3	C		03 ON-OFF-ON	B 220V 氖灯(蓝色) 220V Neon Lamp	02 1 0	3 PCB (RIGHTANGLE)	A 灰色 Gray	A 灰色 Gray
4	C1		04 (ON)-OFF	C 6V 钨丝灯(绿色) 6V Tungsten Bulb	03 0 I	4 PCB (RIGHTANGLE)	Y 黄色 Yellow	Y 黄色 Yellow
5	D		11 ON-OFF	D 12V 钨丝灯(绿色) 12V Tungsten Bulb	04 I O II	6 4.8mm TAB 0.8mm THICK	R 红色 Red	R 红色 Red
6	D1		12 ON-OFF	E 110V 氖灯(蓝色) 110V Neon Lamp	05 .	7 PCB (RIGHTANGLE)	W 白色 White	W 白色 White
7	D1A			F 24V 钨丝灯(红色) 24V Tungsten Bulb	06 -	8 PCB (RIGHTANGLE)	L 蓝色 Blue	L 蓝色 Blue
8	E			I 12V LED 灯(绿色) 12V LED Lamp	07 I	9 PCB (RIGHTANGLE)	O 橘黄色 Orange	O 橘黄色 Orange
9	F			J 220V LED 灯(红色) 220V LED Lamp	08 OFF		P 紫色 Purple	P 紫色 Purple
10	F1			L 24V LED 灯(红色) 24V LED Lamp	09 1 0			
11	G			M 220V 氖灯(红色) 220V Neon Lamp	10 0 I			
12	K			N 110V 氖灯(红色) 110V Neon Lamp	11 - -			
13					12 1 1			
14					13 .			
15					14 3			
16					15			
17					16			
					17 0			